GENERAL INFORMATION ABOUT IC1000,2000,3000 SERIES COVERS

Your new interior cover is designed to protect the windshield, dashboard, steering wheel and other components of the interior from the damaging rays of the sun, tree sap, and other elements in the air when your convertible top is down. This cover is NOT designed or intended to be used as protection from rain or other forms of heavy condensation or moisture.

Most IC 1000,2000,3000 series covers are positioned over the windshield, under the wipers and attach inside the trunk or rear deck lid with tube filled webbing straps. There are some variations in the methods of attachment due to the differences in vehicle style. PLEASE NOTE: not all of the following characteristics will necessarily apply to your installation. Inspect the cover and review how it will align with the various attachment points on your vehicle.

Elastic or he	ook and loop around or through the door handles.
Hook and lo	oop around windshield wiper arms.
Hook and lo	oop under/around mirrors.

Most covers are designed to be used with the windows DOWN. However, if you encounter difficulty aligning the front or rear of the cover, adjust the windows.

INSTALLATION PROCEDURE

- 1. Unfold the cover and locate the word FRONT with the part number stenciled below.
- 2. Center the cover over the windshield and interior. Position the cover under the wiper blades.
- 3. Open the trunk or rear deck lid. Position the webbing straps sewn on the rear of the cover inside the opening. Close the trunk or deck lid, making sure the tube filled webbings remain inside.
- 4. At this time you should be able to determine if your style of cover requires the side windows to be **up** or **down.**
- 5. Attach the cover at the door handle locations. (if applicable).
- 6. Check for attachment around wiper blades or outside mirrors.
- 7. If applicable, bend the tabs around the top of the rear fender and wheel well openings. Adjust the tension on the straps so the cover is snug.
- 8. Readjust all attachments if needed.

CARE INSTRUCTIONS

Wash in warm water with mild soap. Rinse in warm or cold water. For best results, wash and rinse over a chair, fence or clothes line. Dry naturally. Mechanical dry with **air only** setting. **Do not use heat.**IMPORTANT WARNING: In rare cases when a rain storm is followed by an extreme drop in temperature to below freezing, it is possible for the cover to become frozen to a layer of ice created between the body of the vehicle and the cover. **DO NOT** attempt to remove the cover immediately. It is recommended to pour WARM WATER over the cover and SLOWLY remove it from the vehicle, carefully inspecting the surface of both the cover and the vehicle during the removal process.